DynaIndustrial

Case Study: Comprehensive Roll Rebuilding




1. Introduction: The Critical Role of Caster Rolls in Steel Manufacturing

Continuous casting represents a foundational process in modern steel manufacturing, and the rolls that guide the molten metal through its transformation are subject to some of the most demanding operational conditions in heavy industry. These rolls must endure immense mechanical stress, continuous thermal cycling, and a highly corrosive, high-temperature environment. This relentless degradation leads to predictable but complex failure modes, including surface wear, thermal fatigue cracking, and dimensional inaccuracies. The cost and lead time associated with procuring new rolls are significant, making expert rebuilding and repair an essential service for steel mills seeking to maintain operational continuity and cost efficiency.

DynaIndustrial has positioned itself as a long-term partner in this critical sector, with over 49 years of specialized experience in rebuilding continuous caster segment rolls. This report outlines the company's end-to-end process, demonstrating how its strategic investment in advanced technology and its deep understanding of material science combine to restore rolls to their original specifications, or even to improve their long-term performance. The methodology is a systematic progression from initial cleaning and preparation through precision welding, thermal treatment, and final quality control, a comprehensive approach that justifies DynaIndustrial's standing as an industry leader.

2. Stage 1: Disassembly and the Strategic Advantage of Automated Cleaning

The Problem and DynaIndustrial's Solution

The initial phase of any roll rebuilding project is crucial, as it lays the foundation for all subsequent operations. It begins with the careful disassembly of the roll by experienced millwrights, a step that requires an understanding of complex industrial machinery. Following disassembly, the challenge shifts to thoroughly cleaning the roll to remove all traces of scale, lubricants, and contaminants that have accumulated during service. Failure to achieve a pristine surface at this stage can lead to weld defects, porosity, and an inadequate bond between the new material and the base metal. Traditional manual cleaning methods are often labor-intensive, time-consuming, and inconsistent, posing a risk to the final product's quality.

DynaIndustrial addresses these challenges with a purpose-built, automated solution. The process utilizes a Better Engineering F5000 LXP-ZX parts washer. This substantial machine is equipped with a rotating table (Image 1) that ensures every surface of the component is subjected to a powerful and uniform cleaning process without the need for manual handling. The parts washer's automated operation not only guarantees a superior cleaning result but also significantly increases efficiency and reduces labor requirements.

DynaIndustrial
3326 Faithfull Ave | Saskatoon, SK | S7K 8H1 | (306) 933-4303
277 Sherwood Road | RM of Sherwood, SK | S4K 0A8 | (306) 359-7088

Image 1

3. Stage 2: Precision Preparation and the Power of Large-Scale CNC Machining

The Necessity of Undercutting

After cleaning, the roll is transported to the machine shop for undercutting. This is a critical preparatory step that serves a dual purpose. First, it involves the complete removal of the existing hardfacing material and any underlying fatigued or damaged base metal. Caster rolls are subject to repetitive thermal and mechanical stresses that can lead to microcracking below the surface, which is undetectable until the outer layer is removed. Second, undercutting creates a geometrically precise, stable, and clean surface, which is essential for ensuring proper fusion and adherence of the new weld overlay. This process demands a machine with exceptional power, rigidity, and dimensional accuracy to handle components that are often massive and heavy.

DynaIndustrial's Technological Edge

The precision of this preparatory phase is guaranteed by DynaIndustrial’s use of large Computer Numerical Control (CNC) lathes, such as the Mazak Nexus 550, which are designed specifically for handling large-scale turning operations (Image 2). The Mazak Nexus 550M is a robust machine with impressive specifications, including a powerful 45 kW (60 HP) main spindle motor that delivers a maximum torque of 5163 ft-lbs. This capability allows for high-efficiency material removal even at low speeds, which is ideal for the demanding, heavy cuts required to remove worn roll material.

Image 2

The selection of a machine like the Nexus 550 demonstrates a strategic understanding of process optimization. The Nexus 550M is capable of both turning and milling operations. This dual functionality is highly advantageous as it allows for the completion of complex preparatory tasks, such as creating specific geometrical features or keyways, without having to remove the roll from the machine and move it to another workstation. This consolidation of processes reduces setup time, minimizes the risks associated with handling large components, and ensures a higher degree of dimensional consistency. The advanced, automated, and precise nature of CNC technology ensures that the undercut roll meets strict geometric requirements, which is a prerequisite for a flawless weld deposit.

4. Stage 3: The Science of Advanced Welding and Hard Surfacing

The Importance of Pre-heating

Following the preparatory machining, the roll is moved to a controlled welding cell. Before any new material is applied, the roll must be pre-heated to a specific temperature. This step is a fundamental metallurgical requirement for preventing thermal shock, which can lead to cracking, and for ensuring optimal fusion between the base metal and the weld deposit. DynaIndustrial utilizes a "state of the art, highly efficient induction heater" for this purpose (Image 3). The induction oven is a custom-built unit from Thermal Tech & Temp, controlled by a Miller Proheat35 system.

Image 3

The Miller Proheat35 controller is a key piece of technology, as it is a self-adjusting system. This means it automatically adapts its internal parameters to match the thermal characteristics of the oven and the workpiece, ensuring temperature consistency even as ambient conditions change. The operator sets the desired temperature, and the system intelligently maintains it, reducing the potential for human error. The operation manual recommends setting the control thermocouples at least 25 degrees Fahrenheit higher than the required part temperature. This practical measure ensures that the high-mass steel roll reaches its target soak temperature efficiently by leveraging the slightly warmer air inside the insulated oven.

The Multi-Pass Welding Strategy

Once the pre-heating is complete, the welding process begins. This is not a single-pass operation but a meticulously engineered, multi-layer application.

Image 4

The Buttering Pass

The first layer is a “buttering pass” using a specialized wire like **BUF-S**. The selection of a specific buffer material is a testament to DynaIndustrial's metallurgical expertise. The purpose of this layer is not primarily to provide surface hardness, but to serve as a high-integrity intermediate layer between the core of the roll and the final hardfacing deposit. BUF-S is a submerged arc welding consumable designed to produce a weld deposit with excellent impact resistance and high strength after post-weld heat treatment. This foundational layer prevents crack and propagation under service stress, safeguarding the roll core against catastrophic failure.

DynaIndustrial
3326 Faithfull Ave | Saskatoon, SK | S7K 8H1 | (306) 933-4303
277 Sherwood Road | RM of Sherwood, SK | S4K 0A8 | (306) 359-7088

The Hard Surfacing Layers

After the buttering pass, several layers of hard surfacing material are applied. The choice of welding wire at this stage is a critical engineering decision based on the specific operational environment of the customer's mill.

The following table summarizes the properties and applications of the different hardfacing wires discussed:

Table 1: Comparison of Hard Surfacing Consumables

Consumable	Material Type	Key Property	Application
BUF-S	Submerged Arc Buffer Wire	Excellent impact resistance and high strength.	Buffer material for cladding industrial mill rolls
CHROMECORE 414N-S	Martensitic Stainless Steel	Optimized for corrosion, wear, galling, and thermal fatigue resistance.	Hardfacing continuous casting rolls
CHROMECORE 414NX-S	Martensitic Stainless Steel with Nb, V	Enhanced resistance to temper, oxidation, creep, and thermal stress.	Cladding steel mill rolls subject to repetitive thermal stress
Stoody ThermaClad 423	Martensitic Stainless Steel	Greatest resistance to thermal fatigue cracking and corrosion.	Weld overlay on continuous caster rolls
Stoody ThermaClad 423H	Martensitic Stainless Steel	Higher initial hardness compared to Stoody 423; resists thermal fatigue cracks.	Weld overlay on continuous caster rolls

The CHROMECORE 414N-S wire is a nitrogen-containing martensitic stainless steel deposit, ideal for hardfacing parts that endure a combination of corrosion, abrasive wear, and thermal shocks. For even more demanding applications, CHROMECORE 414NX-S is a more advanced alloy that includes Niobium (Nb), Vanadium (V), and Rare Earth Materials (REM). These additives provide enhanced resistance to temper, oxidation, and creep, making it particularly suitable for rolls that experience repetitive thermal stresses. Similarly, the difference between Stoody ThermaClad 423 and 423H highlights a tactical choice: the H variant has a higher carbon content for greater initial hardness, while the standard version offers superior resistance to thermal fatigue cracking.

This sophisticated selection process is guided by DynaIndustrial's qualified welding engineers, who perform an in-depth analysis of a roll's specific service conditions and failure history to recommend the optimal hardfacing material. This consultative approach ensures that the repair not only restores the roll but also potentially improves its operational life.

DynaIndustrial
3326 Faithfull Ave | Saskatoon, SK | S7K 8H1 | (306) 933-4303
277 Sherwood Road | RM of Sherwood, SK | S4K 0A8 | (306) 359-7088

5. Stage 4: Post-Weld Heat Treatment (PWHT) and Rigorous Quality Control

The Critical PWHT Step

After the final welding layers are applied, the rolls undergo a crucial post-weld heat treatment (PWHT) in a gas-fired oven. The purpose of this step is threefold: to stress-relieve the welded material, to temper the martensitic structure of the hardfacing deposit, and to ensure the final mechanical properties and desired hardness are achieved.

The technical data sheets for the welding consumables illustrate the importance of this stage. The properties of BUF-S, for instance, are explicitly listed as being "After PWHT @ 1100∘F for 6 hours", with a tensile strength of 123,000 PSI and a yield strength of 89,000 PSI. This indicates that the final structural integrity of the buffer layer is dependent on this heat treatment. Similarly, the temper curve provided for CHROMECORE 414N-S shows a direct correlation between the PWHT temperature and the final hardness of the deposit. This level of process control allows DynaIndustrial to precisely engineer the final metallurgical state of the roll to meet the specific requirements of its application.

Quality Assurance

Following the PWHT process, the rolls are subjected to a thorough inspection. This quality control step is performed to ensure that the correct and consistent hardness has been achieved along the entire roll face. This rigorous verification process is essential for guaranteeing that the finished product will perform reliably under the demanding conditions of a steel mill.

6. Stage 5: Finish Machining and Final Precision

The final stage of the roll rebuilding process is finish machining. The rolls are returned to the machining cell, where one of the large CNC lathes, like the Mazak Nexus 550, is used to machine the roll back to the customer's exact specifications.

This step is a direct application of the precision capabilities discussed earlier. The importance of this phase cannot be overstated, as the final roll finish and the precision of the roll diameter directly impacts the quality of the slab or strand produced by the caster. A precise diameter ensures consistent shell thickness and prevents breakouts, while a high-quality surface finish is necessary to produce a defect-free product. By utilizing the same high-precision CNC equipment for both the initial undercutting and the final machining, DynaIndustrial ensures dimensional consistency and repeatability throughout the entire rebuilding cycle.

DynaIndustrial
3326 Faithfull Ave | Saskatoon, SK | S7K 8H1 | (306) 933-4303
277 Sherwood Road | RM of Sherwood, SK | S4K 0A8 | (306) 359-7088

7. Conclusion: The DynaIndustrial Differentiators

This case study demonstrates that DynaIndustrial’s roll rebuilding service is a comprehensive, multi-stage, and technologically advanced process. The company's capabilities extend far beyond simple repair.

DynaIndustrial's key differentiators include:

Process Efficiency and Cost Savings: The use of experienced millwrights combined with an automated parts washer not only streamlines the initial cleaning process but also provides a clear and quantifiable return on investment.

Advanced Equipment: The strategic investment in large-scale, dual-function CNC lathes enables high-precision preparation and finishing of even the largest rolls, while reducing setup and handling time.

Metallurgical Expertise: The process is guided by qualified welding engineers who select and apply specific materials, such as buffer passes like BUF-S and application-specific hardfacing wires like CHROMECORE 414NX-S, to address unique operational challenges and enhance the roll's long-term performance.

Rigorous Process Control: The use of modern induction heating and a controlled post-weld heat treatment process ensures the final metallurgical properties of the roll are precisely engineered to specification.

Decades of Experience: With over 49 years in the industry, DynaIndustrial possesses an institutional understanding of the critical importance of roll finish and precision diameters, which directly translates to a high-quality finished product for its customers.

By combining these elements, DynaIndustrial provides a level of quality and reliability that ensures the integrity of its customers' operations and solidifies its position as a trusted partner in the steel manufacturing industry.

About DynaIndustrial:

DynaIndustrial is a fully integrated engineering and manufacturing company, specializing in large custom design/build projects and heavy industrial equipment repair. For over 49 years, DynaIndustrial has been successfully solving the steel mills most challenging problems with innovative engineered designs, turnkey solutions and quality products that increase productivity and safety and decrease maintenance downtime.

DynaIndustrial
3326 Faithfull Ave | Saskatoon, SK | S7K 8H1 | (306) 933-4303
277 Sherwood Road | RM of Sherwood, SK | S4K 0A8 | (306) 359-7088